

MODEL	KĄT OSTRZA	DŁUGOŚĆ CIĘCIA	MAX GRUBOŚĆ CIĘCIA	LICZBA CIĘĆ/MIN	DŁUGOŚĆ	SZEROKOŚĆ	WYSOKOŚĆ	GŁĘBOKOŚĆ GARDŁA	WYSOKOŚĆ ROBOCZA	LICZBA STOPERÓW	MOC SILNIKA	SZYBKOŚĆ ZDERZAKA	POJEMNOŚĆ ZBIORNIKA OLEJU	WAGA
PRIMACUT			St42		A	F	H	D	G					
	(°)	mm	mm	1/min	mm	mm	mm	mm	mm	szt	kW	mm/s	litr	kg
2606	0,5 ... 2,5	2600	6	20 ... 35	3300	2650	2165	350	790	12	11	200	150	6600
3106	0,5 ... 2,5	3100	6	18 ... 32	4100	2650	2165	350	790	15	11	200	150	7600
3110	0,5 ... 2,5	3100	10	14 ... 25	4030	2700	2290	350	805	15	22	200	300	11300
3113	0,5 ... 2,5	3100	13	12 ... 23	4050	2700	2290	350	805	15	22	200	400	12700
3116	0,5 ... 2	3100	16	10 ... 20	4090	2900	2475	350	880	15	30	200	500	17300
3120	0,5 ... 2	3100	20	9 ... 16	4125	3065	2530	350	880	15	37	200	500	21250
3125	0,5 ... 2,5	3100	25	7 ... 13	3950	2850	2800	350	1000	19	55	200	600	26500
4106	0,5 ... 2,5	4100	6	16 ... 25	5120	2665	2165	350	790	19	11	200	300	7600
4110	0,5 ... 2,5	4100	10	12 ... 22	4935	2700	2290	350	805	19	22	200	300	13200
4113	0,5 ... 2,5	4100	13	11 ... 20	4950	2720	2440	350	805	19	22	200	400	15700
4116	0,5 ... 2	4100	16	9 ... 18	5050	2900	2475	350	880	19	30	200	500	19500
4120	0,5 ... 2	4100	20	6 ... 12	5080	3065	2530	350	880	19	37	200	500	23700
6106	0,5 ... 2,5	6100	6	13 ... 19	7120	2665	2165	350	790	32	15	200	300	17500
6110	0,5 ... 2,5	6100	10	11 ... 17	6950	2700	2290	350	805	32	30	200	300	25500
6113	0,5 ... 2	6100	13	7 ... 11	7175	2700	2290	350	965	32	30	200	400	32900
6116	0,5 ... 2	6100	16	8 ... 14	7080	2900	2475	350	1000	32	37	200	500	36500
6120	0,5 ... 2	6100	20	5 ... 10	7125	3065	2530	350	1050	32	45	200	500	43500

